



Charisma Panels

Specification Sheet

These premium matte hardcoat acrylic panels are UV resistant, anti-fingerprint and have anti-bacterial properties. The Acrylic surface is from Austria - a premium European product. Their scratch and abrasion resistance is significantly higher than other standard matte surfaces. They are available in six colours to suit your upcoming cabinetry project. - White, Black, Charcoal, Blue, Slate Grey & Revival Green. The substrate is the ultimate, European Multiply Birch Core or an E0 MDF Core.

The Charisma Birch Panel colours are only available on one face except for the Black, which is also available on two faces as well. All the Charisma MDF Panels are available with two faces.

Product Info

Code	Core	Sheet Size	Thickness	Name	Colour	Faces	Weight
H4019-BK-2F	Birch 2F	2440 x 1220	17.5mm	Black	[Black Panel]	Double Sided	42 kg
H4019-BK	Birch	2440 x 1220	17.5mm	Black		Face Back	42 kg
H4020-BK-2F	E0 MDF	2440 x 1220	17.5mm	Black	[White Panel]	Double Sided	42 kg
H4019-WH	Birch	2440 x 1220	17.5mm	White		Face Back	42 kg
H4020-WH-2F	E0 MDF	2440 x 1220	17.5mm	White	[Charcoal Panel]	Double Sided	42 kg
H4019-CH	Birch	2440 x 1220	17.5mm	Charcoal		Face Back	42 kg
H4020-CH-2F	E0 MDF	2440 x 1220	17.5mm	Charcoal	[Blue Panel]	Double Sided	42 kg
H4019-BLU	Birch	2440 x 1220	17.5mm	Blue		Face Back	42 kg
H4020-BLU-2F	E0 MDF	2440 x 1220	17.5mm	Blue	[Slate Grey Panel]	Double Sided	42 kg
H4019-SG	Birch	2440 x 1220	17.5mm	Slate Grey		Face Back	42 kg
H4020-SG-2F	E0 MDF	2440 x 1220	17.5mm	Slate Grey	[Revival Green Panel]	Double Sided	42 kg
H4019-RG	Birch	2440 x 1220	17.5mm	Revival Green		Face Back	42 kg
H4020-RG-2F	E0 MDF 2F	2440 x 1220	17.5mm	Revival Green	Double Sided	42 kg	

Technical Specs

Finish	Smooth Matte (Anti-fingerprint & Stain-resistant)
Core	European Birch BB multiply core, WBP EN34-2 Class 3
Origin	Austria
Environment	Sustainable Plantation

Handling & Application/ Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Temperature variation may cause internal stresses causing previously flat sheets to bow. Precautions are taken to minimize this effect. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack with enough support to prevent sagging. Cover the pallet to protect top and edges.

